

3W, AC/DC converter



FEATURES

- Ultra-wide 90 - 528V AC or 100 - 745V DC input voltage range
- Accepts AC and/or DC input (dual-use of same terminal)
- Operating ambient temperature range: -40°C to +70°C
- Compact size, high power density
- I/O isolation test voltage 3000 VAC
- Used in electricity, instrumentation area
- Output short circuit, over-current protection
- UL/IEC/EN62368 safety approved

LD03-16Bxx Series is one of Mornsun's compact size power converters. It features ultra-wide input voltages, taking both DC and AC input, low power consumption, high efficiency, high reliability, reinforced insulation. The converters meet IEC/UL/EN62368 and FCC part 15 standards. The converters are widely used in industrial control, instrumentation and electric power applications, requiring extremely wide input voltage range and meeting UL and CE and EMC certification. For extremely harsh EMC environment, we recommend using the application circuit show in Design Reference of this datasheet.

Selection Guide

| Certification | Part No. | Output Power | Output Voltage and Current (Vo/Io) Nominal | Efficiency at 230VAC (%) Typ. | Capacitive Load (μF) Max. |
|---------------|------------|--------------|--|-------------------------------|---------------------------|
| UL/CE/CB | LD03-16B03 | 1.65W | 3.3V/500mA | 63 | 6000 |
| | LD03-16B05 | 2.5W | 5V/500mA | 70 | 5000 |
| | LD03-16B09 | 3W | 9V/333mA | 73 | 5000 |
| | LD03-16B12 | | 12V/250mA | 76 | 3000 |
| | LD03-16B15 | | 15V/200mA | 76 | 1500 |
| | LD03-16B24 | | 24V/125mA | 76 | 1000 |

Note: * Part No. with suffix of "A2S" means chassis mounting and suffix of "A4S" means DIN-Rail mounting.

Input Specifications

| Item | Operating Conditions | Min. | Typ. | Max. | Unit |
|---------------------------------|----------------------|-------------------------|------|------|------|
| Input Voltage Range | AC input | 90 | -- | 528 | VAC |
| | DC input | 100 | -- | 745 | VDC |
| Input Frequency | | 47 | -- | 63 | Hz |
| Input Current | 115VAC | -- | -- | 0.12 | A |
| | 230VAC | -- | -- | 0.06 | |
| | 480 VAC | -- | -- | 0.04 | |
| Inrush Current | 115VAC | -- | 9 | -- | A |
| | 230VAC | -- | 15 | -- | |
| | 480 VAC | -- | 27 | -- | |
| Leakage Current | 230VAC/50Hz | 0.25mA RMS typ. | | | |
| Recommended External Input Fuse | | 2.0A slow-blow required | | | |
| Hot Plug | | Unavailable | | | |

Output Specifications

| Item | Operating Conditions | | Min. | Typ. | Max. | Unit |
|----------------------------|--------------------------------------|------------|-----------------------------------|-------|------|------|
| Output Voltage Accuracy | LD03-16B03 | | -- | ±6 | -- | % |
| | Others | | -- | ±5 | -- | |
| Line Regulation | Full load | LD03-16B03 | -- | ±2.5 | -- | |
| | | Others | -- | ±1.5 | -- | |
| Load Regulation | 10% - 100% load | | -- | ±2.5 | -- | |
| Ripple & Noise* | 20MHz bandwidth (peak-to-peak value) | | -- | -- | 180 | mV |
| Temperature Coefficient | | | -- | ±0.15 | -- | %/°C |
| Stand-by Power Consumption | 230VAC Input | | -- | -- | 0.3 | W |
| | 528VAC Input | | -- | -- | 0.5 | |
| Short Circuit Protection | | | Hiccup, continuous, self-recovery | | | |
| Over-current Protection | | | 150 - 300%Io, self-recovery | | | |
| Minimum Load | | | 10 | | | % |
| Hold-up Time | 230VAC input | | -- | 40 | -- | ms |

Note: *The "parallel cable" method is used for ripple and noise test, please refer to AC-DC Converter Application Notes for specific information. See also output capacitor connection in Fig.1.

General Specifications

| Item | Operating Conditions | | Min. | Typ. | Max. | Unit |
|-----------------------|--------------------------------|----------------------------------|--------------------------------|------|------|--------|
| Isolation Test | Input-output | Electric Strength Test for 1min. | 3000 | -- | -- | VAC |
| Operating Temperature | See temperature derating curve | | -40 | -- | +70 | °C |
| Storage Temperature | | | -40 | -- | +105 | |
| Storage Humidity | | | -- | -- | 85 | %RH |
| Soldering Temperature | Wave-soldering | | 260 ± 5°C; time: 5 - 10s | | | |
| | Manual-welding | | 360 ± 10°C; time: 3 - 5s | | | |
| Power Derating | +55°C ~ +70°C | | 2.0 | -- | -- | % / °C |
| | -40°C ~ -20°C (90-165VAC) | | 3.0 | -- | -- | |
| Safety Standard | | | IEC62368/UL62368/EN62368 | | | |
| Safety Certification | | | IEC62368/UL62368/EN62368 | | | |
| Safety Class | | | CLASS II | | | |
| MTBF | | | MIL-HDBK-217F@25°C ≥ 300,000 h | | | |

Mechanical Specifications




| | | |
|----------------|--|--------------------------|
| Case Material | Black plastic, flame-retardant and heat-resistant (UL94 V-0) | |
| Dimension | DIP package | 50.80 x 25.40 x 15.16 mm |
| | A2S chassis mounting | 76.00 x 31.50 x 23.96 mm |
| | A4S Din-Rail mounting | 76.00 x 31.50 x 28.56 mm |
| Weight | DIP package | 30g (Typ.) |
| | A2S chassis mounting | 50g (Typ.) |
| | A4S Din-Rail mounting | 70g (Typ.) |
| Cooling Method | Free air convection | |

Electromagnetic Compatibility (EMC)

| | | | |
|---|---|---|------------------|
| Emissions* | CE | CISPR32/EN55032/FCC part 15 CLASS A | |
| | | CISPR32/EN55032/FCC part 15 CLASS B (See Fig. 2 for recommended circuit) | |
| | RE | CISPR32/EN55032/FCC part 15 CLASS A | |
| | | CISPR32/EN55032/FCC part 15 CLASS B (See Fig. 2 for recommended circuit) | |
| Immunity | ESD | IEC/EN 61000-4-2 Contact $\pm 6\text{KV}$ /Air $\pm 8\text{KV}$ | Perf. Criteria B |
| | RS | IEC/EN 61000-4-3 10V/m (See Fig. 2 for recommended circuit) | perf. Criteria A |
| | EFT | IEC/EN 61000-4-4 $\pm 2\text{KV}$ | perf. Criteria B |
| | | IEC/EN 61000-4-4 $\pm 4\text{KV}$ (See Fig. 2 for recommended circuit) | perf. Criteria B |
| | Surge | IEC/EN 61000-4-5 line to line $\pm 1\text{KV}$ | perf. Criteria B |
| | | IEC/EN 61000-4-5 line to line $\pm 2\text{KV}$ / line to ground $\pm 4\text{KV}$ (See Fig. 2 for recommended circuit) | perf. Criteria B |
| | CS | IEC/EN61000-4-6 3Vr.m.s (See Fig. 2 for recommended circuit) | perf. Criteria A |
| Voltage dips, short interruptions and voltage variations immunity | IEC/EN61000-4-11 0%, 70% (See Fig. 2 for recommended circuit) | perf. Criteria B | |

*This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

Product Characteristic Curve



Note:

- ① With an AC input between 90 - 110V/480 - 528VAC and a DC input between 100 - 155V/675 - 745VDC, the output power has to be derated as per the temperature derating curves;
- ② This product is suitable for applications using natural air cooling; for applications in closed environment please consult factory or one of our FAE.

Design Reference

1. Typical application




Fig. 1

| Element model | MOV1 | C1 | C2 (required) | FUSE (required) | TVS | | |
|---------------|---------|-----------|---------------|-----------------|----------|---------|---------|
| LD03-16B03 | S14K550 | 0.1μF/50V | 100μF/16V | 2.0A | SMBJ7.0A | | |
| LD03-16B05 | | | 47μF/16V | | | | |
| LD03-16B09 | | | 47μF/35V | | SMBJ12A | | |
| LD03-16B12 | | | | | | SMBJ20A | |
| LD03-16B15 | | | | | | | SMBJ20A |
| LD03-16B24 | | | | | | | |

Output Filter Components:

We recommend using an electrolytic capacitor with high frequency, and low ESR rating for C2 (refer to manufacture’s datasheet). Choose a capacitor voltage rating with at least 20% margin, in other words not exceeding 80%. C1 is a ceramic capacitor used for filtering high-frequency noise and TVS is a recommended suppressor diode to protect the application in case of a converter failure.

2. EMC compliance recommended circuit






Fig. 2

| Element model | Component values |
|---------------|-------------------------|
| MOV1 | S14K550 |
| MOV2, MOV3 | S07K300 |
| LCM | 10mH |
| CX | 0.22μF/530VAC |
| CY1, CY2 | 470pF/500VAC |
| R1, R2 | 12Ω/2W |
| FUSE | 2.0A slow-blow required |

3. For additional information please refer to the application notes on www.mornsun-power.com



Dimensions and Recommended Layout



| Pin-Out | |
|---------|----------|
| Pin | Function |
| 1 | AC(N) |
| 2 | AC(L) |
| 3 | -Vo |
| 4 | +Vo |

Note:
Unit :mm[inch]
Pin diameter tolerances : ± 0.10 [± 0.004]
General tolerances: ± 0.50 [± 0.020]


A2S Dimensions




Note:
Unit: mm[inch]
Wire range: 24-12 AWG
Tightening torque: Max 0.4 N·m
General tolerances: ± 1.00 [± 0.039]

A4S Dimensions

THIRD ANGLE PROJECTION 



| Pin-Out | |
|---------|----------|
| Pin | Function |
| 1 | AC(N) |
| 2 | AC(L) |
| 3 | -Vo |
| 4 | +Vo |



Note:
Unit: mm[inch]
Wire range: 24-12 AWG
Tightening torque: Max 0.4 N·m
Installed on DIN RAIL TS35
General tolerances: ±1.00[±0.039]

Notes:

1. For additional information on Product Packaging please refer to www.mornsun-power.com. Packaging bag number: 58220003(DIP package); 58220022 (A2S/A4S package);
2. If the product is not operated within the required load range, the product performance cannot be guaranteed to comply with all parameters in the datasheet;
3. Unless otherwise specified, parameters in this datasheet were measured under the conditions of $T_a=25^{\circ}\text{C}$, humidity<75% with nominal input voltage and rated output load;
4. In order to improve the efficiency at light load, there will be audible noise generated, but it does not affect product performance and reliability;
5. All index testing methods in this datasheet are based on our company corporate standards;
6. We can provide product customization service, please contact our technicians directly for specific information;
7. Products are related to laws and regulations: see "Features" and "EMC";
8. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

MORNSUN Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China
Tel: 86-20-38601850 Fax: 86-20-38601272 E-mail: info@mornsun.cn www.mornsun-power.com